

TUYAU FLEXIBLE SUPERIEUR EN 856 4SH - ISO 3862 4SH
FLEXIBLE HYDRAULIC HOSE EXCEED EN 856 4SH - ISO 3862 4SH

4SH

APPLICATIONS :



RENFORT:

4 nappes acier

									
Code <i>Code</i>	Type	ID		OD	Max WP	Min BP	Min BR	Weight	Jupe
		in	mm	mm	bar	bar	mm	kg/m	
FG412A0000	TFDR4SH-12	3/4"	19	32	420	1780	210	1,572	004N-12/X Series
FG416A0000	TFDR4SH-16	1 "	25,4	38,4	385	1750	220	2,104	004N-16/X Series
FG420A0000	TFDR4SH-20	1.1/4"	31,8	45,8	350	1400	400	2,55	004N-20/X Series
FG424A0000	TFDR4SH-24	1.1/2"	38,1	53,5	300	1250	560	3,225	004N-24/X Series
FG432A0000	TFDR4SH-32	2 "	50,8	68	250	1000	700	4,6	004N-32/X Series

TUYAU INTERNE : Caoutchouc synthétique, extrudé entier sans joints, d'épaisseur uniforme.

REVÊTEMENT : Caoutchouc synthétique anti-abrasif, résistant aux huiles, aux carburants et aux conditions atmosphériques. MSHA.

FLUIDE RECOMMANDÉ : Huiles minérales et biologiques, à base d'eau glycolée, eau, lubrifiants, air comprimé.

TEMPÉRATURE DE FONCTIONNEMENT : DE -40 À +100°C (INTERMITTENT 120°C).