

R4

TUYAU FLEXIBLE SAE 100R4
FLEXIBLE HYDRAULIC HOSE SAE 100R4

APPLICATIONS :



RENFORT:

2 tresses textile + 1 spire acier

									
Code <i>Code</i>	Type	ID		OD	Max WP	Min BP	Min BR	Weight	Jupe
		in	mm	mm	bar	bar	mm	kg/m	
FGA1900000	TFS0004-12	3/4"	19	29	21	84	60	0,61	012N-12
FGA2500000	TFS0004-16	1 "	25	35	17	68	75	0,75	012N-16
FGA3200000	TFS0004-20	1.1/4"	32	42	14	56	100	0,92	012N-20
FGA3800000	TFS0004-24	1.1/2"	38	48,5	105	42	127	1,14	012N-24
FGA5000000	TFS0004-32	2 "	51	63	7	28	150	1,81	012N-32
FGA6300000	TFS0004-40	2.1/2"	63,5	76	4	16	178	2,43	012N-40
FGA7600000	TFS0004-48	3 "	76	89	4	16	230	2,99	012N-48

TUYAU INTERNE : Caoutchouc synthétique résistant à l'huile.

REVÊTEMENT : Caoutchouc synthétique résistant aux huiles, aux carburants et aux conditions atmosphériques.

FLUIDE RECOMMANDÉ : Fluides hydrauliques à base de pétrole, à base d'eau glycolée, lubrifiants.

TEMPÉRATURE DE FONCTIONNEMENT : de -40 à +100°C en continu +70°C pour les fluides à base d'eau.